
CONTRACTOR

3255

eression at



RUGGED, RELIABLE PERFORMANCE.

For consumers who want value and functionality, plus the everyday dependability of a LiftMaster[®].

Durable 1/2 HP motor and industrial-strength chain drive provide steady performance.

- 100-watt lighting
- Meets all UL325 requirements
- 4-year motor warranty

ACCESSORIES INCLUDED



Multi-Function Control Panel

The standard in control. Controls garage door and turns opener lights on/off from inside the garage. Locks out radio signals while you're away. Includes adjustable light timer and illuminated oversized push button.



Security+® 1-Button Remote Control

With rolling code technology, you are assured of a new code with every use. Every time you come and go, your code changes to one of over 100-billion new codes, never to be repeated.

At Chamberlain, safety is a major part of our mission.

It's our commitment to you and, quite simply, the way we produce products every day. Our LiftMaster[®] products are designed to move the largest door in your home, safely, securely and by always putting safety first.



3255

UNSURPASSED SAFETY AND SECURITY

All LiftMaster® garage door openers are manufactured with the highest level of safety and monitoring systems to ensure safe operation.

- The Protector System® safety sensors reverse the door automatically if the infrared beam is broken, before contact is made.
- Patented technology detects when a door spring breaks and triggers the motor to reverse the door to the full open position.
- Sensing technology will stop the door from closing if contact is made with a person or object.
- \bullet Security+® Rolling Code Technology assures a new code is sent every time the remote is used.
- Patented PosiLock[®] system ensures the door remains securely locked when it is closed.
- Opener light turns on automatically when The Protector System[®] safety infrared beam is broken.

ENHANCE YOUR LIFESTYLE WITH OPTIONAL ACCESSORIES



know for sure the door is closed

Lets you know whether the garage door is open or closed from any room in the house. A flashing red light shows the door is open; a glowing green light indicates the door is closed.

GARAGE DOOR MONITOR (915LM)

enter without a key

Open your garage door without using a remote control and close with just the push of a button. Also can be programmed with a temporary entry code for friends and service people.



WIRELESS KEYLESS ENTRY with SECURITY +[®](377LM)



access on the go

Operates up to 3 garage doors. Turns garage door opener lights on and off. Fits on keychain or in a pocket or purse.

MINI 3-BUTTON REMOTE CONTROL with SECURITY +[®] (370LM)

put control where you want it

For people who want a second control in their garages. A light control button turns garage door opener lights on and off. Auxiliary button can be programmed to open and close a second garage door.





park perfectly every time

The high-tech solution that helps you park perfectly in your garage! As you pull into your garage the laser is activated and projected onto the dashboard, making it easy to park in the same spot every time.

LASER GARAGE PARKING ASSIST (975LM)

SPECIFICATIONS

STANDARD SPECIFICATIONS DIMENSIONS

Installed Length: 124" Maximum Door Opening: 7' 6"* Headroom Clearance Required: 2" *Up to 10' with optional 8' or 10' rails

CARTONS Number of Cartons: 2

Carton 1 Dimensions and Contents: 20" x 12" x 10" Multi-Function Control Panel

Multi-Function Control Panel 371LM Remote Control Garage Door Opener Head The Protector System[®] Carton 2 Dimensions and Contents: 10' 4" x 5" x 5" Assembled Solid-Steel T-Rail

SECURITY+® RADIO CONTROLS

Coding System: Smart Receiver Code Button and Indicator Light Operating Range: 150' (approximately) Operating Temperature: -40°F to Battery (remote control): 3-Volt -40°F to 150°F 371LM Standard Remote Control with Security+® Anti-Burglary Coding

CONVENIENCE/SAFETY

The Protector System® Emergency/Quick Release Automatic Trolley Reconnect Ventilation/Pet Opening Down Safety Reverse Up Safety Stop Door Open/Beam Broken/Lights On PosiLock[®]

ELECTRICAL SPECIFICATIONS POWER

Voltage: 120V AC, 60Hz; Wattage: 540; Current Rating: 4.5 UL Listings: Yes; Length of Line Cord: 4' (3-prong) LOGIC TYPE

Solid-State Microcontroller with Built-in Surge Suppressor LIGHTING

umber of Bulbs: 1 Maximum Wattage: 100 Length of Light Delay: 4 1/2 Minutes Type of Light Delay: Solid-State

MECHANICAL SPECIFICATIONS

MOTOR : 1/2 Horsepower: 1/2 RPM: 1,625 Thermal Protection: Automatic Lubrication: Permanent

DRIVE MECHANISM Drive Means: Full Chain Reduction Means: Gear 16:1

Door Linkage: Adjustable Door Arm ADJUSTMENTS lent External Up and Down Limit: External

TRAVEL RATE Approximately SHIPPING WEIGHTS Head: 22 Lbs. Rail: Full Chain—20 Lbs.

MATERIALS

Rail: Solid-Steel T Trolley: Steel

4-YEAR MOTOR WARRANTY

1 year on all other parts. For more information, refer to owner's manual. LiftMaster[®] garage door openers meet all current state and federal regulations and UL safety regulations as of data of manufacture. as of date of manufacture.



The in-vehicle universal remote control. See your automobile dealer for availability.



World's #1 Installed Garage Door Opener THE CHAMBERLAIN GROUP, INC. 845 Larch Avenue • Elmhurst, IL 60126





I.C./F.C.C. Certified

©2007 LM 3255 06/07 namberlain Group, Inc. Printed in U.S.A.

WARNING: Garage doors and openers can be dangerous if not properly installed, tested and operated. Children should be supervised by an adult whenever in or around the garage area.

