

# 8165

1/2 HP AC CHAIN DRIVE GARAGE DOOR OPENER



## Rugged, Reliable Performance

### Connectivity

- **MyQ® Technology** enables you to securely monitor and control your garage door opener and houselights with your smartphone, tablet or computer.
- **Alerts** can be received as email or pop-up (push) notifications on your mobile device so that you always know the status of your garage door and houselights.
- **MyQ mobile app** is a free download requiring no activation or subscription fees.

### Performance

- **P3™ Motors** from LiftMaster® are reliable, durable and powerful – designed specifically for your needs.
- **1/2 HP AC motor** with industrial-strength chain drive provides steady performance and lifting power.
- **Energy-efficient** operation consumes up to 75% less power in standby mode.
- **4-year motor warranty** and 1-year parts warranty.

### Safety and Security

- **Security+ 2.0™** safeguards your household – with every click a new code is sent to the garage door opener so that the door opens only for you.
- **PosiLock®** locks down your garage door by electronically monitoring against a forced opening.
- **Alert-2-Close** warning system provides audible and visual warnings when the garage door is about to close when using MyQ Technology.
- **The Protector System®** has safety sensors that project a light beam across the garage door opening, automatically reversing the door if anything interrupts the beam.

### Included Accessories:



#### 1-Button Remote Control (891LM)

Allows you to control a single garage door opener, gate operator or MyQ Light Accessory. With Security+ 2.0™, you are assured of a new code with every use.



#### Multi-Function Control Panel (882LM)

Allows you to program remote controls, keypads and MyQ Light Accessories from the control panel. Includes lockout remote controls for added security.

### Optional Accessories:



#### Internet Gateway (828LM)

Connect your MyQ-Enabled Garage Door Opener and Accessories to the Internet with this device and the free MyQ app.



#### Ceiling Mount (195LM)

Give your garage the style it's been missing by hiding the wires and cords with this sleek ceiling mount. Works in most standard garages.



#### Remote Light Control (825LM)

Allows you to control any lamp with your garage door opener remote control or smartphone via the Internet Gateway and the free MyQ app.



#### Door and Gate Monitor (829LM)

Enables you to monitor and close up to four garage doors or gates from any room in your house.

## SPEC SHEET

### STANDARD SPECIFICATIONS

#### DIMENSIONS

Installed Length: 124"  
 Maximum Door Opening: 7' 6" \*  
 Headroom Clearance Required: 2"  
 \*Up to 10' with optional 8' or 10' rails

#### CARTONS

Number of Cartons: 2  
 Carton 1: Dimensions and Contents:  
 - 20" x 12" x 10"  
 - 882LM Multi-Function Control Panel  
 - 891LM 1-Button Remote Control  
 - Garage Door Opener Head  
 - The Protector System®  
 Carton 2: Dimensions and Contents:  
 - 10' 4" x 5" x 5"  
 - Assembled Solid-Steel T-Rail

#### SECURITY+® RADIO CONTROLS

Coding System: Smart Receiver Code Button and Indicator Light  
 891LM 1-Button Remote Control  
 Operating Range: 200' (approximately)  
 Operating Temperature: -40°F to 150°F  
 Battery (remote control): 3-Volt Lithium  
 Frequency:  
 - Remote Control: 310, 315 & 390 MHz Tri-Band  
 - Receiver: Frequency Agile on 310, 315 & 390 MHz  
 Security+ 2.0™ Anti-Burglary Coding

#### CONVENIENCE / SAFETY

PosiLock® Alert-2-Close  
 Emergency/Quick Release  
 Automatic Trolley Reconnect  
 Ventilation/Pet Opening  
 Down Safety Reverse  
 Up Safety Stop  
 Door Open/Beam Obstructed/Lights On  
 The Protector System®  
 Maintenance Alert System

### ELECTRICAL SPECIFICATIONS

#### POWER

Voltage: 120V AC, 60Hz  
 Current Rating: 6.0A  
 UL Listings: Yes  
 Length of Line Cord: 4' (3-prong)

#### ENERGY EFFICIENCY

Approximately 1 Watt Power in Standby Mode\*  
 Enhanced CFL (Compact Fluorescent) Compatible  
 \*Standby Mode at down limit, work lights off

#### LOGIC TYPE

Solid State Microcontroller with Built-in Surge Suppressor

#### LIGHTING

Number of Bulbs: 1  
 Maximum Wattage: 100  
 Length of Light Delay: 4 1/2 Minutes  
 Type of Light Delay: Solid-State  
 Enhanced CFL (Compact Fluorescent) Compatible, Max 26 Watts

### MECHANICAL SPECIFICATIONS

#### MOTOR

Horsepower: 1/2  
 RPM: 1,625  
 Thermal Protection: Automatic  
 Lubrication: Permanent

#### DRIVE MECHANISM

Drive Means: Full Chain  
 Reduction Means: Gear 16:1  
 Door Linkage: Adjustable Door Arm

#### ADJUSTMENTS

Force: Electronic/Internal Auto Force  
 Limit: Internal Electronic

#### TRAVEL RATE

Approximately 7"/second

#### SHIPPING WEIGHTS

Head: 22 lbs.  
 Rail: Full Chain—20 lbs.

#### MATERIALS

Chassis: Steel  
 Rail: Solid-Steel T  
 Trolley: Steel

#### WARRANTY

4 Year Motor Warranty  
 1 Year Parts Warranty

#### HOMELINK® Compatible (version 4.0 or higher)\*

\*May require an external adapter depending on the model and year of your vehicle.  
 Visit [homelink.com](http://homelink.com) for additional information.