

DC CHAIN/CABLE DRIVE GARAGE DOOR OPENER

Simple, reliable performance in a compact design.



FEATURES

RELIABLE DC Motor

CHAIN/CABLE Drive

RELIABLE

P3
MOTORS®

CUSTOMIZED DC MOTOR WITH SOFT START/STOP ACTION.

CHAIN/CABLE SQUARE STEEL RAIL (SSR) SYSTEM FOR EFFICIENT OPERATION AND STANDARD PERFORMANCE.

WARRANTY 1-YEAR MOTOR, PARTS AND ACCESSORIES.

SECURE

Security+ 2.0®

INCREASES REMOTE CONTROL RANGE AND REDUCES INTERFERENCE FOR CONSISTENT OPERATION.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

INCLUDED ACCESSORIES:

DOOR CONTROL BUTTON

Opens and closes the garage door and controls the opener's lights.



883LM

1-BUTTON REMOTE CONTROL

Operates a single opener or MyQ® Light Accessory.



891LM

POWERFUL ADD-ONS:

MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.



374UT

GARAGE DOOR AND GATE MONITOR

Monitors and closes up to 4 garage doors from any room in the house.



829LM

MyQ GARAGE

Enables smartphone control of garage door openers with photo eyes.



821LM

MASTERFUL ENGINEERING.

MOTOR

- 12V DC
- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed
- 4' Power Cord (3-Prong)

OPENER HEAD DIMENSIONS

Length	15"
Width	8"
Height	5.5"



MECHANICS

- Steel Chassis, Square Steel Rail (SSR) and Trolley
- Full Chain/Cable Drive Mechanism (63:1 Gear Reduction and Adjustable Door Arm)
- Auto-Force Adjustment for Changing Weather and Environmental Conditions
- Electronic Limits for Easy Setup
- DC Logic Board with Built-In Surge Suppressor (For Replacement Logic Boards, Order Part Number 047DCT)

INSTALLED RAIL DIMENSIONS

Rail Options	7'	8'
Installed Length	128"	140"
Max. Opening	7'6"	8'6"

Headroom Clearance Required: 2"

7"

Per second for door to move upward

SPEED

7"

Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0® RADIO CONTROLS

1-Button Remote Control (891LM)



Operating Temperature: -40°F to 150°F
Frequency:

- Remote Control: 310, 315 and 390 MHz Tri-Band
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Security+ 2.0 Anti-Burglary Coding

SECURITY+ 2.0 ENCRYPTED CONTROLS

- Door Control Button (883LM)
- Program Remote Controls
- Turn Opener Lights On and Off

COMPATIBILITY

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

MyQ®

- MyQ Garage (821LM) is required to enable monitoring and control of the garage door opener and lighting controls via smartphone, tablet or computer.

ELECTRICAL

LIGHTING



- 1 60-Watt Lightbulb
- Adjustable Time, Solid-State Delay
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 23 Watts

ENERGY USAGE

- Approximately 6.8-Watt Power in Standby Mode*
- *Occurs at Down Limit When Opener's Lights Turn Off

SHIPPING.

SHIPPING WEIGHT (in lbs.)



CARTONS (2)

CARTON 1: 20" x 11.38" x 8"

- Door Control Button (883LM)
- 1-Button Remote Control (891LM)
- Garage Door Opener Head (8010)

- The Protector System® Safety Reversing Sensors

CARTON 2: 124" x 4" x 3.5" (7', 1607LM)

136.375" x 4" x 3.5" (8', 1608LM)

CONVENIENCE AND SAFETY.



- Hands-Free Work Lights On
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Break Turns Lights On