



Speed-Master[®] 2600 L High Performance Door

Industrial and commercial, NEMA 4X Smart Start[™] NXT control box
High cycle interior or exterior door openings up to 24'0" w x 24'0" h



Speed-Master® 2600 L

Industrial high cycle applications up to 24'0" w x 24'0" h

Ideal for demanding industrial areas

Demanding industries such as manufacturing, distribution, transit, steel plants, airports, etc., that have high cycle door requirements, will benefit from the simple, reliable design of the Speed-Master® 2600 L. Design advantages such as zero moving parts with the guide tracks and direct-drive motor, support minimized maintenance and the walk-away dependability busy operations need. For exterior mounting doors, options like a roll and motor cover along with motor / gearbox heater make it possible to accommodate high traffic exterior door applications during cold weather, for added energy savings as compared to use of conventional roll-up doors.



Optional roll / motor cover

NEMA 4X Smart Start™ NXT simplifies installation

The Speed-Master® 2600 L now includes our Smart Start™ NXT, next generation, NEMA 4X, control box as standard and without a price increase. The updated control box has a simplified wiring configuration, is more powerful, and has fewer components and cables as compared to the original Smart Start™. A distribution block accepts the activation and protection device wiring; main power cables feed through pre-drilled holes on the bottom of the box where the individual wires, with pre-wired removable terminal blocks, simply plug into the circuit board. There are extra ports on the control board allowing for firmware upgrades and future expansion. A USB port is available for maintenance monitoring.



NEMA 4X Smart Start™ NXT control box

Features

Application	Interior or exterior.
Model	2600 L.
Size range	Max. 24'0" w x 24'0" h / max. 400 sq. ft.
Technology	Direct-drive, sectional panel.
Operating speed	Opening 36" / sec. Closing 30" / sec.
Panel	Patented, sectional panel design, made of ultra tough, reinforced, puncture resistant 1/8" thick Bulldog XT material, 90 oz. sq. yd. Panels are connected with heavy-duty aluminum hinge profiles. Colors: orange, blue, black, gray and white.
Resistance to wind load	Up to 6.7 psf * / Maximum 90 mph** (In closed position). *Based on DASMA wind load testing 108-2012-6. **Calculated in accordance with ASCE 7-10 exposure category B. Independent Testing Agency tested. Maximum door sizes tested. All doors with wind locks.
Vision	Two full-width, clear PVC starting approximately 36" off floor.
Safety device	8'0" high light grid built into guide tracks.
Control	NEMA 4X Smart Start™ NXT with a 208 v to 575 v / 3-phase / 60 Hz voltage input. Step-up transformer required for supply voltages under 460 v.
Emergency	Chain hoist.
Warranty	5 & 2 Year: Motor/gearbox (excluding catch) and panel material, 5 years, materials & workmanship. All other mechanical and electrical components free from defects, 2 years.

Take a look at our website for more information!

